

New Multibibliography Package^{*}

Boris Veytsman[†] Michael Cohen[‡]

2015/07/27, v1.04

Abstract

The `nmbib` package is a rewrite of `multibibliography` package providing multiple bibliographies with different sorting. The new version offers a number of citation commands, streamlines the creation of bibliographies, ensures compatibility with the `natbib` package, and provides other improvements.

Contents

1	Introduction	2
2	User Guide	3
2.1	Usage Summary	3
2.2	Options	3
2.3	Setting up	3
2.4	Citation commands	4
2.5	Printing the bibliographies	5
2.6	Hyperlinks	5
2.7	Advanced customization	5
2.8	Auxillary script	7
3	Implementation	8
3.1	Declarations	8
3.2	Loading packages	8
3.3	Preliminary Definitions and opening aux files	8
3.4	Citation commands	9
3.5	Processing bibliography	16
3.6	Ending the Style	18

^{*}©2015 Michael Cohen and Boris Veytsman

[†]borisv@lk.net

[‡]mcohen@u-aizu.ac.jp

1 Introduction

The list of cited works accompanying a scholarly work is not just a technical appendix or a subtle way to avoid accusations of plagiarism. Rather, it is an organic part of the work, telling the user a story about the field of study and showing why the given work is an organic part of it. There are several ways to tell the story, and accordingly there are several ways to organize the list of references. One can tell it accordingly to logical development of ideas, so the order of citations follows the order they are mentioned in the paper. This leads to the “unsorted” style of references, usual in physics and mathematics papers and books. Alternatively, one can choose to tell the story as the story of people behind the ideas, ordering the citations alphabetically by author names. This is the order used in humanities and other fields. Yet another possibility is to tell the story in the chronological order. The chronological order of citations is not widely used, with the important exception of resumes and CVs, but it has its own advantages.

In the times BC (Before Computers), difficulties in manual creation of reference lists discouraged presentation of more than one such list. Now we can easily have as many lists as we want. Accordingly we can have not one, but several lists of references, each telling a different story. The package `multibibliography` (Cohen et al., 2013a,b) provided just this: multiple bibliographies with the same references arranged in different orders, with hyperlinks between entries. However, this package had various limitations, including: the fixed format of typesetting citations in text, the limitation on the possible BibTeX styles. Also, it requires post-processing by a Perl script.

This package tries to lift these limitations. It provides the following improvements over the original `multibibliography`:

1. A Perl postprocessing is no longer needed: all processing is done by BibTeX.
2. The user can work with familiar `natbib` (Daly, 2009) commands `\citet`, `\citeauthor`, `\citeyear`, `\citenum`.
3. Any `natbib`-compatible `.bst` file can be used for formatting the bibliography provided that it has the right sorting of entries (note that the provided style gives `natbib`-compatible chronological ordering).
4. The style is much more customizable than that produced by `multibibliography`.
5. Hyperlinks between the entries are improved.

Note about the name. The letter n in the package name can be interpreted as

1. New multibibliography style, or
2. Natbib-compatible multibibliography style, or even
3. N -ordering multibibliography style, with N being a usual mathematical moniker for “many”.

2 User Guide

2.1 Usage Summary

The simplest way to use the package is the following:

1. Add to the preamble of your `.tex` file

```
\usepackage{nmbib}
\multibibliography{FILE1, FILE2, ...}
\multibibliographystyle{timeline}{STYLE1}
\multibibliographystyle{sequence}{STYLE2}
\multibibliographystyle{authors}{STYLE3}
```

2. Use `natbib` commands such as `\cite`, `\citet`, `\citeauthor`, `\citeyear`, and `\citenum`. The command `\citeall` creates a “full citation”, showing the author, year, and number of the citation.
3. Put in your document at the places where you want the bibliography the commands `\printbibliography{timeline}`, `\printbibliography{sequence}`, and `\printbibliography{authors}`.
4. Run `latex` on the `tex` file. This will create, besides the standard auxiliary file `FILE.aux`, three new files: `FILE-timeline.aux`, `FILE-sequence.aux` and `FILE-authors.aux`.
5. Run `bibtex` on each of the three auxiliary files mentioned above:

```
bibtex FILE-timeline
bibtex FILE-sequence
bibtex FILE-authors
```

6. Run `latex` on the `tex` file at least twice (this is a `natbib` requirement).

Below we discuss these commands in more detail as well as customization commands.

2.2 Options

The `nmbib` package internally uses `natbib` (Daly, 2009) for citation formatting. The options used for `nmbib` are sent to `natbib`.

2.3 Setting up

`\multibibliography` The list of BIB_TE_X databases to be used for references is set by the command `\multibibliography{\langle bibfile1, bibfile2, ... \rangle}`. Note that the similar command `\bibliography` in standard L^AT_EX performs *two* functions: it sets up the databases

`\multibibliographystyle`

and prints the bibliography. The command `\multibibliography`, on the other hand, performs only one function: the setting up of the databases. The bibliographies themselves are printed by the command `\printbibliography`, discussed below. Therefore the `\multibibliography` command can be issued anywhere in the file, including the preamble.

The standard `\bibliographystyle` command sets the bibliography style of the reference list. Since `nmbib` generates several bibliographies, the corresponding command is more versatile: `\multibibliographystyle{<type>}{<style>}`, where `type` is the type of the bibliography

timeline: Chronologically ordered list.

sequence: Sequentially ordered list.

authors: Alphabetic list, ordered according to authors' names.

and `{<style>}` is the corresponding BIBTEX style. The style, of course, must sort the entries in the proper order.

The package can accommodate any `natbib` BIBTEX style, including `unsrtnat`, `plainnat`, and `abbrvnat`. It may work with other styles, but success is not guaranteed. The BIBTEX styles supplied with the package offer additional hyperlink features; if you do not use `hyperref` or do not care for the links between the different reference lists, you probably do not need these features.

There are three citation styles provided with the package:

chronoplainnm: Similar to `plainnat`, but sorting entries in chronological order (using year, month and day if the latter two are available) and providing links to other lists from the body of the entries.

plainnm: Similar to `plainnat`, but providing links to other lists from the body of the entries. The sorting is alphabetical by authors' names, as in `plainnat`.

unsrtnm: Similar to `unsrtnat`, but providing links to other lists from the body of the entries. The order of entries is the order of citations, as in `unsrtnat`.

2.4 Citation commands

All citations commands defined in `natbib` can be used: `\cite`, `\citemenum`, `\citealn`, `\citet`, `\Citet`, etc. The `nmbib` package adds a couple of new commands, described here.

`\citealn`

The commands `\citealn{<keys>}` is the alternative `\citemenum` command: it puts square brackets around its argument.

`\citeall`

The command `\citeall{<keys>}` produces citations with authors' names, years, and sequence numbers, similar to that produced by the `\cite` command in the `multibibliography` package. To reproduce the behavior of that package, just put in the preamble of your document

`\let\cite\citeall`

The starred command `\citeall*` is similar to `\citeall` with the following difference: if `\citeall` prints the shortened author list for papers with multiple authors (“Jones et. al.”), `\citeall*` prints the full list (“Jones, Smith, and Brown”).

2.5 Printing the bibliographies

`\printbibliography` The command `\printbibliography{<type>}` prints the bibliography. The argument is the type of bibliography—`timeline`, `sequence`, or `authors` (see the explanation above).

You can put this command anywhere in your file; the corresponding bibliography will be printed in this place. You can use all three possible lists, any two, or even one. The only limitation is that the “base type” list must be included. (See Section 2.7 for the discussion of base type.)

2.6 Hyperlinks

The `nmbib` package tries to fully exploit features of `hyperref` package (Rahtz and Oberdiek, 2012). Links from and between citations should work “smartly”: links from authors’ names go into the alphabetic list, links from the publication years go into the chronological list, and links from the citation numbers go into the sequential list.

`\nmbibRedirectLinks` Of course, the user might include only some of the three possible lists. In this case some links become “dangling.” The command `\nmbibRedirectLinks {<source_type>} {<target_type>}` redirects the links that otherwise go to the list `{<source_type>}` to the list `{<target_type>}`. For example, if a chronological list is not included, the command `\nmbibRedirectLinks{timeline}{authors}` makes the links from the publication year go into the alphabetical list of publications.

`\nmbibLink` The clickable links themselves are created with the help of the command `\nmbibLink{<citation>}{<type>}{<text>}`. This command is available to the user, which enables constructions like

The idea was proposed by `\citet{Thor10}`. Note the assumption of differentiability in `\nmbibLink{Thor10}{authors}{his paper}`.

In this example “his paper” becomes a hyperlink to the paper in the alphabetical list.

The links created with `\nmbibLink` respect the redirections set by the command `\nmbibRedirectLinks`.

2.7 Advanced customization

`\timelinerefname` The commands `\refname` (for article-like classes) and `\bibname` (for book-like classes) retain the names of the bibliography. The `nmbib` package defines three macros `\TYPErefname` and three commands `\TYPEbibname`, `TYPE` being
`\sequencerefname`
`\authorsrefname`
`\timelinebibname`
`\sequencebibname`
`\authorsbibname`

`\multibibliographyfilename`, `\nmbibBasetype`, `\nmbibSetCiteall`, `\nmbibRedirectLinks`, `\nmbibLink`, `\nmbibKEY`, `\nmbibNAME`, `\nmbibDATE`, and `\nmbibNUM` are the main commands of the package. They are described in the following sections.

`timeline`, `sequence`, or `authors`. These macros can be redefined with the usual `\renewcommand`. For example, for a German article, one might use

```
\renewcommand{\timelinerefname}{Chronologische Referenzliste}
\renewcommand{\sequencerefname}{Sequenzielle Referenzliste}
\renewcommand{\authorsrefname}{Alphabetische Referenzliste}
```

By default the package creates three auxillary files with the following file names: `FILE-timeline.aux`, `FILE-sequence.aux`, and `FILE-authors.aux`. The command `\multibibliographyfilename{<type>}{<name>}` changes this default. Here `{<type>}` is `timeline`, `sequence`, or `authors`, and `{<name>}` is the file name. The default setting is equivalent to

```
\multibibliographyfilename{timeline}{\jobname-timeline}
\multibibliographyfilename{sequence}{\jobname-sequence}
\multibibliographyfilename{authors}{\jobname-authors}
```

This command may be present only in the preamble of a document.

Suppose an author published several works in the same year. They need to be distinguished in the text and bibliography. In the standard author-year styles this is done by adding a suffix after the year: if we want to cite three works by A. U. Thor published in 2013, they are respectively cited as Thor (2013a), Thor (2013b), and Thor (2013c). When we have only one reference list, the choice of suffixes is simple: the first work becomes 2013a, the second 2013b, etc. But how should we deal with the situation of several subbibliographies? The order of these references in different lists could be different, so the same work could get different labels in different lists.

To prevent this confusion, only one reference list is used to construct the labels. We call the corresponding list type the *base type*. By default it is `sequence`, but this might be changed (and should be chaged if the user does not include sequential list) with the command `\nmbibBasetype{<type>}`, with `{<type>}` being `timeline`, `sequence`, or `authors`. The list chosen as a base type must be included with the `\printbibliography` macro.

Package `natbib` defines citation aliases: you can use “Paper I” or “Paper II” as aliases for some papers. Normally hyperlinks from aliases go into the alphabetic list; however, you can change it with the special type `alias` in `\nmbibRedirectLinks`, for example,

```
\nmbibRedirectLinks{alias}{timeline}
```

The format of the `\citeall` and `\citeall*` macros can be changed by the command `\nmbibSetCiteall{<pattern>}`, where `{<pattern>}` sets the citation format. The pattern can use any punctuation, `\nmbibLink` command and the special tokens `\nmbibKEY`, `\nmbibNAME`, `\nmbibDATE` and `\nmbibNUM`, which are substituted by the citation information. For example, the default format is established by the command

```
\nmbibSetCiteall{\nmbibLink{\nmbibKEY}{authors}{\nmbibNAME}
  (\nmbibLink{\nmbibKEY}{timeline}{\nmbibDATE})
  [\nmbibLink{\nmbibKEY}{sequence}{\nmbibNUM}]}
```

which produces the following result: [Daly \(2009\)](#) [3].

\nmbibSetBiblabel

The command `\nmbibSetBiblabel{<type>}{pattern}` is used to set the format of the label in the reference list of the given type. The `{<pattern>}` parameter uses the same tokens as `\nmbibSetCiteall`. The default is

```
\nmbibSetBiblabel{timeline}{[\nmbibDATE:
  \nmbibLink{\nmbibKEY}{authors}{\nmbibNAME};
  \nmbibLink{\nmbibKEY}{sequence}{\nmbibNUM}]}
\nmbibSetBiblabel{authors}{[\nmbibNAME\
  (\nmbibLink{\nmbibKEY}{timeline}{\nmbibDATE});
  \nmbibLink{\nmbibKEY}{sequence}{\nmbibNUM}]}
\nmbibSetBiblabel{sequence}{[\nmbibNUM:
  \nmbibLink{\nmbibKEY}{authors}{\nmbibNAME}
  (\nmbibLink{\nmbibKEY}{timeline}{\nmbibDATE})]}
```

To suppress the label for any type, use an empty pattern: `\nmbibSetBiblabel{authors}{()}`. To use numerical labels only for a sequential list, issue `\nmbibSetBiblabel{sequence}{[\nmbibNUM]}` etc.

nmbibYearSuffixOff
nmbibYearSuffixOn

If there are several works with the same authors and year, the package adds suffixes to the year numbers, like 2003a and 2003b. By default these suffixes are printed both in the labels *and* in the bibliographic entries themselves. The command `\nmbibYearSuffixOff` deletes these suffixes from the bibliography entries (but not from labels). The command `\nmbibYearSuffixOn` restores them.

2.8 Auxillary script

To integrate the package with IDEs like T_EXShop, we provide a simple script `nmbibtex` which compiles all bibliographies. Its usage is very simple:

```
nmbibtex FILE
```

where FILE is the file name without prefixes.

3 Implementation

3.1 Declarations

We start with declaration, who we are:

```
1 <style>\NeedsTeXFormat{LaTeX2e}
2 {*gobble}
3 \ProvidesFile{nmbib.dtx}
4 {/gobble}
5 <style>\ProvidesPackage{nmbib}
6 {*style}
7 [2015/07/27 v1.04 Multibibliography support for LaTeX]
```

3.2 Loading packages

We send all options to `natbib`

```
8 \DeclareOption*{\PassOptionsToPackage{\CurrentOption}{natbib}}
9 \ProcessOptions\relax
```

and call `natbib`

```
10 \RequirePackage{natbib}
```

3.3 Preliminary Definitions and opening aux files

`\NMBIB@types` The comma-separated collection of types: right now we have three of them.

```
11 \def\NMBIB@types{timeline,sequence,authors}
```

`\multibibliographyfilename` Defining the names for bibliography files

```
12 \def\multibibliographyfilename#1#2{%
13   \expandafter\edef\csname NMBIB@#1@filename\endcsname{#2}%
14 @onlypreamble{\multibibliographyfilename}
```

`\NMBIB@timeline@filename` The file names for aux files (without .aux extension)

```
15 @for@tempa:=\NMBIB@types\do{%
16   \expandafter\multibibliographyfilename{@tempa}{\jobname-\@tempa}}
```

`\NMBIB@timeline@aux` We introduce the output streams

```
17 @for@tempa:=\NMBIB@types\do{%
18   \expandafter\newwrite\csname NMBIB@\@tempa @aux\endcsname}
```

We open and close them at the beginning and end of the document

```
19 \AtBeginDocument{%
20   \if@files
21     @for@tempa:=\NMBIB@types\do{%
22       \immediate\openout\csname NMBIB@\@tempa @aux\endcsname
23       \csname NMBIB@\@tempa @filename\endcsname.aux
24       \immediate\write\csname NMBIB@\@tempa @aux\endcsname{\relax}%
25     }
26 \AtEndDocument{%
```

	<pre> 27 \if@filesw 28 \@for\@tempa:=\NMBIB@types\do{% 29 \immediate\closeout\csname NMBIB@\@tempa @aux\endcsname}% 30 \fi} </pre>
\multibibliographystyle	Define the bibliographystyle for the corresponding list. Note the trick with \begindocumenthook, which allows us to write the files only after the files are opened.
	<pre> 31 \def\multibibliographystyle#1#2{% 32 \ifx\@begindocumenthook\@undefined\else 33 \expandafter\AtBeginDocument 34 \fi 35 \if@filesw 36 \immediate\write\csname NMBIB@#1@aux\endcsname{% 37 \string\bibstyle{#2}}% 38 \fi}% </pre>
\multibibliography	Writing bibliography data to the aux files
	<pre> 39 \def\multibibliography#1{% 40 \ifx\@begindocumenthook\@undefined\else 41 \expandafter\AtBeginDocument 42 \fi 43 \if@filesw 44 \@for\@tempa:=\NMBIB@types\do{% 45 \immediate\write\csname NMBIB@\@tempa @aux\endcsname 46 {\string\bibdata{#1}}% 47 \fi}% </pre>
\nmbibBasetype	The macro \nmbibBasetype sets the type that is used for the citation command:
\NMBIB@bibcite@type	<pre> 48 \def\nmbibBasetype#1{\gdef\NMBIB@bibcite@type{#1}} 49 \nmbibBasetype{sequence} </pre>
\NMBIB@timeline@cite@suffix	The macro \NMBIB@TYPE@cite@suffix keeps the suffix added to the hyperlink
\NMBIB@sequence@cite@suffix	cite:
\NMBIB@authors@cite@suffix	<pre> 50 \@for\@tempa:=\NMBIB@types\do{% 51 \expandafter\edef\csname NMBIB@\@tempa 52 @cite@suffix\endcsname{\@tempa}% 53 \def\NMBIB@alias@cite@suffix{authors}} </pre>
\nmbibRedirectLinks	The macro \nmbibRedirectLinks{\langle from \rangle}{\langle to \rangle} redefines the suffix:
	<pre> 54 \def\nmbibRedirectLinks#1#2{% 55 \expandafter\edef\csname NMBIB@#1@cite@suffix\endcsname{#2}} </pre>

3.4 Citation commands

\NAT@set@cites	The command \NAT@set@cites is used by natbib to set up citation styles. It is added to the begindocument hook, so we need to disable it here:
	<pre> 56 \def\NAT@set@cites{} </pre>

```

57 \let\@cite\NAT@cite
58 \let\@citex\NAT@citex
59 \let\@biblabel\NAT@biblabel
60 \let\@bibsetup\NAT@bibsetup
61 \let\NAT@space\NAT@spacechar
62 \let\NAT@penalty\@empty
63 \renewcommand\NAT@idxtxt{\NAT@name\NAT@spacechar\NAT@open\NAT@date\NAT@close}
64 \def\natexlab#1{#1}

\ifNMBIB@printyearsuffix Whether to print the year suffix
65 \newif\ifNMBIB@printyearsuffix
66 \NMBIB@printyearsuffixtrue

\nmbibYearSuffixOn Switching on the suffixes
67 \def\nmbibYearSuffixOn{\NMBIB@printyearsuffixtrue}

\nmbibYearSuffixOff Switching off the suffixes
68 \def\nmbibYearSuffixOff{\NMBIB@printyearsuffixfalse}

\NAT@sort@cites The command \NAT@sort@cites sorts the citations and writes them to the aux file. We want to write them to another file instead.
69 \renewcommand\NAT@sort@cites[1]{%
70   \let\NAT@cite@list\@empty
71   \@for\@citeb:=#1\do{\expandafter\NAT@star@cite\@citeb\@{}}
72   \if@filesw
73     \@for\@tempa:=\NMBIB@types\do{%
74       \expandafter\immediate\expandafter\write\expandafter
75       \csname NMBIB@\@tempa\@aux\endcsname
76       \expandafter{\expandafter\string\expandafter\citation\expandafter{\NAT@cite@list}}}
77   \fi
78   \gdef\@tempa{\NAT@sort}\z@{%
79     \expandafter\NAT@sort@cites@\expandafter{\NAT@cite@list}}
80   }{}%
81 }%

\nmbibcitenumber This command is written to the main aux file and contains the number of the citation (since different lists may produce different numbers). We store the number in the macro \nmbib@num@KEY\@extra@binfo. We also use natbib warnings about multiple citations.
82 \def\nmbibcitenumber#1#2{%
83   \@ifundefined{nmbib@num@#1\@extra@binfo}{\relax}{%
84     \NAT@citemultiple
85     \PackageWarningNoLine{natbib}{Citation '#1' multiply defined}%
86   }%
87   \global\@namedef{nmbib@num@#1\@extra@binfo}{#2}%
88 \AtEndDocument{\let\nmbibcitenumber\NMBIB@testnum}

\NMBIB@testnum Testing whether citation number have been changed.
89 \newcommand\NMBIB@testnum[2]{%

```

```

90 \def\nAT@temp{#2}%
91 \expandafter \ifx \csname nmbib@num@#1\@extra@binfo\endcsname\nAT@temp
92 \else
93   \ifNAT@swa \NAT@swafalse
94     \PackageWarningNoLine{natbib}{%
95       Citation(s) may have changed.\MessageBreak
96       Rerun to get citations correct%
97     }%
98   \fi
99 \fi
100 }%

```

\NAT@parse The `natbib` command `\NAT@parse` parses the `\bibcite` arguments and stores them in the corresponding macros. However, the citation number may be wrong since it might be taken from a wrong list. Therefore we use the number from `\nmbibcitenum` instead.

```

101 \let\nAT@parse@orig=\NAT@parse\relax
102 \renewcommand\nAT@parse[1]{\NAT@parse@orig{#1}%
103   \Qifundefined{nmbib@num@#1\@extra@binfo}{\def\nAT@num{0}}{%
104     \edef\nAT@num{\csname nmbib@num@#1\@extra@binfo\endcsname}}}

```

\nmbibLink The command `\nmbibLink{<key>}{<type>}{<text>}` is like `\NAT@hyper@`, but on the user level:

```

105 \def\nmbibLink#1#2#3{%
106   \hyper@natlinkstart{#1\@extra@b@citeb-\csname
107     NMBIB@#2@cite@suffix\endcsname}#3\hyper@natlinkend}

```

\NAT@citexnum We use `\NAT@citexnum` to cite numbers:

```

108 \def\nAT@citexnum[#1][#2]#3{%
109   \NAT@reset@parser
110   \NAT@sort@cites{#3}%
111   \NAT@reset@citea
112   \Qcite{\def\nAT@num{-1}\let\nAT@last@yr\relax\let\nAT@nm\empty
113     \@for\@citeb:=\NAT@cite@list\do
114     {\Qsafe@activestrue
115       \edef\@citeb{\expandafter\Qfirstofone\@citeb\empty}%
116       \Qsafe@activesfalse
117       \Qifundefined{b@\@citeb\@extra@b@citeb}{%
118         \Qreset@font\bfseries?}
119         \NAT@citeundefined\PackageWarning{natbib}{%
120           {Citation '\@citeb' on page \thepage \space undefined}}%
121         \let\nAT@last@num\nAT@num\let\nAT@last@nm\nAT@nm
122         \NAT@parse{\@citeb}%
123         \ifNAT@longnames\Qifundefined{bv@\@citeb\@extra@b@citeb}{%
124           \let\nAT@name=\NAT@all@names
125           \global\Qnamedef{bv@\@citeb\@extra@b@citeb}{}{}%
126         \fi
127         \ifNAT@full\let\nAT@nm\nAT@all@names\else
128           \let\nAT@nm\nAT@name\fi

```

```

129 \ifNAT@swa
130   \@ifnum{\NAT@ctype}>\@ne}{%
131     \@citea
132     \NMBIB@hyper@{alias}{\@ifnum{\NAT@ctype=\tw@}{\NAT@test{\NAT@ctype}}{\NAT@alias}}%
133   }{%
134     \@ifnum{\NAT@cmprs}>\z@}{%
135       \NAT@ifcat@num\NAT@num
136       {\let\NAT@nm=\NAT@num}%
137       {\def\NAT@nm{-2}}%
138       \NAT@ifcat@num\NAT@last@num
139       {\@tempcnta=\NAT@last@num\relax}%
140       {\@tempcnta\m@ne}%
141     \@ifnum{\NAT@nm=\@tempcnta}{%
142       \@ifnum{\NAT@merge}>\@ne}{\NAT@last@yr@mbox}%
143     }{%
144       \advance\@tempcnta by\@ne
145     \@ifnum{\NAT@nm=\@tempcnta}{%
146       \ifx\NAT@last@yr\relax
147         \def\NAT@last@yr{\@citea}%
148       \else
149         \def\NAT@last@yr{--\NAT@penalty}%
150       \fi
151     }{%
152       \NAT@last@yr@mbox
153     }%
154   }%
155 }{%
156   \@tempswatrue
157   \@ifnum{\NAT@merge}>\@ne}{\@ifnum{\NAT@last@num=\NAT@num\relax}{\@tempswafalse}{}}{%
158     \if@tempswa\NAT@citea@mbox\fi
159   }%
160 }%
161 \NAT@def@citea
162 \else
163   \ifcase\NAT@ctype
164     \ifx\NAT@last@nm\NAT@nm \NAT@yrsep\NAT@penalty\NAT@space\else
165       \@citea \NAT@test{\@ne}\NAT@spacechar\NAT@mbox{\NAT@super@kern\NAT@open}}%
166     \fi
167     \if*\#1*\else#1\NAT@spacechar\fi
168     \NAT@mbox{\NMBIB@hyper@{sequence}{\citemumfont{\NAT@num}}}}%
169     \NAT@def@citea@box
170   \or
171     \NMBIB@hyper@citea@space{sequence}{\NAT@test{\NAT@ctype}}%
172   \or
173     \NAT@hyper@citea@space{sequence}{\NAT@test{\NAT@ctype}}%
174   \or
175     \NAT@hyper@citea@space{alias}{\NAT@alias}}%
176   \fi
177 \fi
178 }%

```

```

179      }%
180      \@ifnum{\NAT@cmprs>\z@}{\NAT@last@yr}{}
181      \ifNAT@swa\else
182          \@ifnum{\NAT@ctype=\z@}{%
183              \if*#2*\else\NAT@cmt#2\fi
184          }{%
185              \NAT@mbox{\NAT@@close}%
186          \fi
187      }{#1}{#2}%
188 }%

\NMBIB@hyper@ This is the replacement for \NAT@hyper@
189 \def\NMBIB@hyper@#1#2{%
190   \nmbibLink{\@citeb}{#1}{#2} }

\NMBIB@hyper@citea@ This is the replacement for \NAT@hyper@citea:
191 \def\NMBIB@hyper@citea#1#2{%
192   \citea
193   \NMBIB@hyper@{#1}{#2}%
194   \NAT@def@citea
195 }%

\NMBIB@hyper@citea@space@ The replacement for \NAT@hyper@citea@space
196 \def\NMBIB@hyper@citea@space#1#2{%
197   \citea
198   \NMBIB@hyper@{#1}{#2}%
199   \NAT@def@citea@space
200 }%

\def@NAT@last@yr@ Another natbib macro to redefine
201 \def\def@NAT@last@yr#1{%
202   \protected@edef\NAT@last@yr{%
203     #1%
204     \noexpand\mbox{%
205       \noexpand\hyper@natlinkstart{\@citeb\@extra@b@citeb-\NMBIB@sequence@cite@suffix}%
206       {\noexpand\citenumfont{\NAT@num}}%
207       \noexpand\hyper@natlinkend
208     }%
209   }%
210 }%

\NAT@citea@mbox@ This is used in numerical citations
211 \def\NAT@citea@mbox{%
212   \citea\mbox{\NMBIB@hyper@{sequence}{{\citenumfont{\NAT@num}}}}%
213 }@

\NMBIB@citex@ And now the heart of natbib...
214 \def\NMBIB@citex{%
215   [#1] [#2] #3{%

```

```

216  \NAT@reset@parser
217  \NAT@sort@cites{#3}%
218  \NAT@reset@citea
219  \Ccite{\let\NAT@nm\@empty\let\NAT@year\@empty
220  \@for\@citere:=\NAT@cite@list\do
221  {\@safe@activestrue
222  \edef\@citere{\expandafter\@firstofone\@citere\@empty}%
223  \@safe@activesfalse
224  \@ifundefined{b@\@citere\@extra@b@\citere}{\@citea{%
225  \reset@font\bfseries ?}\NAT@citeundefined
226  \PackageWarning{natbib}}%
227  {Citation ‘\@citere’ on page \thepage\space undefined}\def\NAT@date{}}
228  {\let\NAT@last@nm=\NAT@nm\let\NAT@last@yr=\NAT@year
229  \NAT@parse{\@citere}%
230  \@ifNAT@longnames{\@ifundefined{bv@\@citere\@extra@b@\citere}{%
231  \let\NAT@name=\NAT@all@names
232  \global\@namedef{bv@\@citere\@extra@b@\citere}{}{}}%
233  \fi
234  \@ifNAT@full\let\NAT@nm\NAT@all@names\else
235  \let\NAT@nm\NAT@name\fi
236  \@ifNAT@swa\ifcase\NAT@ctype
237  \if\relax\NAT@date\relax
238  \Ccitea\NMBIB@hyper@{authors}{\NAT@nmfmt{\NAT@nm}}%
239  \NMBIB@hyper@{timeline}{\NAT@date}%
240  \else
241  \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
242  \ifx\NAT@last@yr\NAT@year
243  \def\NAT@temp{\?}%
244  \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
245  {Multiple citation on page \thepage: same authors and
246  year\MessageBreak without distinguishing extra
247  letter,\MessageBreak appears as question mark}\fi
248  \NMBIB@hyper@{timeline}{\NAT@exlab}%
249  \else\unskip\NAT@spacechar
250  \NMBIB@hyper@{timeline}{\NAT@date}%
251  \fi
252  \else
253  \Ccitea\NMBIB@hyper@{authors}{%
254  \NAT@nmfmt{\NAT@nm}%
255  \hyper@natlinkbreak{%
256  \NAT@aysep\NAT@spacechar}\{@citere\@extra@b@\citere}%
257  }%
258  \NMBIB@hyper@{timeline}{\NAT@date}%
259  }%
260  \fi
261  \fi
262  \or\@citea\NMBIB@hyper@{authors}{\NAT@nmfmt{\NAT@nm}}%
263  \or\@citea\NMBIB@hyper@{timeline}{\NAT@date}%
264  \or\@citea\NMBIB@hyper@{alias}{\NAT@alias}%
265  \fi \NAT@def@citea

```

```

266     \else
267         \ifcase\NAT@ctype
268             \if\relax\NAT@date\relax
269                 @citea\NMBIB@hyper@\{authors\}\{NAT@nmfmt{\NAT@nm}\}%
270             \else
271                 \ifx\NAT@last@nm\NAT@nm\NAT@yrsep
272                     \ifx\NAT@last@yr\NAT@year
273                         \def\NAT@temp{{?}}%
274                         \ifx\NAT@temp\NAT@exlab\PackageWarningNoLine{natbib}%
275                             {Multiple citation on page \thepage: same authors and
276                             year\MessageBreak without distinguishing extra
277                             letter,\MessageBreak appears as question mark}\fi
278                         \NMBIB@hyper@\{timeline\}\{NAT@exlab\}%
279                     \else
280                         \unskip\NAT@spacechar
281                         \NMBIB@hyper@\{timeline\}\{NAT@date\}%
282                     \fi
283                 \else
284                     @citea\NMBIB@hyper@\{authors\}%
285                     \NAT@nmfmt{\NAT@nm}%
286                     \hyper@natlinkbreak{\NAT@spacechar\NAT@open\if*#1*\else#1\NAT@spacechar\fi}%
287                         {\@citereb@\extra@b@citereb\}}%
288                     \NMBIB@hyper@\{timeline\}\{NAT@date
289                 }%
290             \fi
291             \fi
292             \or@citea\NMBIB@hyper@\{authors\}\{NAT@nmfmt{\NAT@nm}\}%
293             \or@citea\NMBIB@hyper@\{timeline\}\{NAT@date\}%
294             \or@citea\NMBIB@hyper@\{alias\}\{NAT@alias\}%
295             \fi
296             \if\relax\NAT@date\relax
297                 \NAT@def@citea
298             \else
299                 \NAT@def@citea@close
300             \fi
301             \fi
302         }}\ifNAT@swa\else\if*#2*\else\NAT@cmt#2\fi
303         \if\relax\NAT@date\relax\else\NAT@close\fi\fi\{#1\}{#2\}}
304 \let\@citem\NMBIB@citem

\citealn Alternative numerical citation command:
305 \newcommand\citealn[1]{[\citem{#1}]}

\nmbibSetCiteall Setting the format of \citeall
306 \def\nmbibSetCiteall#1{\def\NMBIB@citeallformat{#1}}
307 \nmbibSetCiteall{\nmbibLink{\nmbibKEY}{authors}\{\nmbibNAME\} %
308   (\nmbibLink{\nmbibKEY}{timeline}\{\nmbibDATE\}) %
309   [\nmbibLink{\nmbibKEY}{sequence}\{\nmbibNUM\}]}

\citeall The full cite command

```

```

310 \DeclareRobustCommand{\citeall
311 {\begingroup\@ifnextchar*\{\NAT@fulltrue\@citeall}{\NAT@fullfalse\@citeall*}}
312 \def\@citeall#1{\@ifnextchar[{\@citeall}{\@citeall[]}}
313 \def\@citeall[#1]{\@ifnextchar[{\@citeall[#1]}{\@citeall[] [#1]}}
314 \def\@citeall[#1][#2]{%
315   \NAT@reset@parser
316   \NAT@sort@cites{#3}%
317   \NAT@reset@citea
318   \@cite{%
319     \@for\@citereb:=\NAT@cite@list\do
320       {\@safe@activestru
321         \edef\@citereb{\expandafter\@firstofone\@citereb\@empty}%
322         \@safe@activesfa
323         \@ifundefined{b@\@citereb\@extra@b@\@citereb}{\@citea{%
324           \reset@font\bfseries ?}\NAT@citeundefined
325             \PackageWarning{natbib}%
326             {Citation '\@citereb' on page \thepage\space undefined}\def\NAT@date{}%
327             {\NAT@parse{\@citereb}}%
328             \ifNAT@full\let\NAT@nm\NAT@all@names\else
329               \let\NAT@nm\NAT@name\fi
330               \edef\nmbibKEY{\@citereb}%
331               \edef\nmbibDATE{\NAT@date}%
332               \edef\nmbibNAME{\NAT@nm}%
333               \edef\nmbibNUM{\NAT@num}%
334               \@citea\NMBIB@citeallformat
335               \def\@citeaf{; }%
336             }}\if*#2*\else\NAT@cmt#2\fi}{#1}{#2}}

```

3.5 Processing bibliography

\timelinerefname	Reference list for chrono ordering
	337 \providecommand{\timelinerefname}{Chronological List of References}
\timelinebibname	Reference list for chrono ordering
	338 \providecommand{\timelinebibname}{Chronological Bibliography}
\sequencerefname	Reference list for sequential ordering
	339 \providecommand{\sequencerefname}{Sequential List of References}
\sequencebibname	Reference list for sequential ordering
	340 \providecommand{\sequencebibname}{Sequential Bibliography}
\authorsrefname	Reference list for alph ordering
	341 \providecommand{\authorsrefname}{Alphabetic List of References}
\authorsbibname	Reference list for alph ordering
	342 \providecommand{\authorsbibname}{Alphabetic Bibliography}

```

\ifNMBIB@writenumber The switch whether to write the citation number to the aux file. Should be true
for sequence, false otherwise.
343 \newif\ifNMBIB@writenumber
344 \NMBIB@writenumberfalse

\NMBIB@setup@authors Set up alphabetical-style reference list
345 \def\NMBIB@setup@authors{%
346   \NMBIB@writenumberfalse}

\NMBIB@setup@timeline Timeline reference list looks like alhpabetical
347 \let\NMBIB@setup@timeline\NMBIB@setup@authors

\NMBIB@setup@sequence Sequential citations are numerical
348 \def\NMBIB@setup@sequence{%
349   \NMBIB@writenumbertrue}

\printbibliography The actual printing of the bibliography of the given type. Note that we need to
reset \natexlabel afterwards—just in case it is used outside the bibliography.
350 \def\printbibliography#1{%
351   \def\NMBIB@current@type{\#1}%
352   \def\biblabel{\csname NMBIB@\#1@biblabel\endcsname}%
353   \edef\NMBIB@current@cite@suffix{\csname NMBIB@\#1@cite@suffix\endcsname}%
354   \csname NMBIB@setup@\#1\endcsname
355   \ifx\NMBIB@current@type\NMBIB@bibcite@type
356     \def\nate xlabel@real##1{\#1}%
357   \else
358     \def\nate xlabel@real##1{\NAT@exlab}%
359   \fi
360   \edef\refname{\csname #1refname\endcsname}%
361   \edef\bibname{\csname #1bibname\endcsname}%
362   \@input{\csname NMBIB@\#1@filename\endcsname.bbl}%
363   \def\nate xlabel##1{\#1}%
}

\bibitem Normally \bibitem is defined as \@lbibitem. We want first to calculate the
biblabel
364 \def\bibitem{\@ifnextchar[\{@lbibitem}{\@lbibitem[]}}%

\@lbibitem The macro \@lbibitem calculates \NAT@exlab and calls \@lbibitem:
365 \def\@lbibitem[#1]{%
366   \let\nate xlabel\nate xlabel@real
367   \NAT@parse{#2}%
368   \def\nmbibKEY{#2}%
369   \edef\nmbibDATE{\NAT@date}%
370   \edef\nmbibNAME{\NAT@name}%
371   \edef\nmbibNUM{\NAT@num}%
372   \@lbibitem[#1]{#2}%
373   \ifNMBIB@printyearsuffix\else\def\nate xlabel##1{}\fi}

```

\NAT@exlab Before the package is loaded, \NAT@exlab should not give an error:

```
374 \providecommand{\NAT@exlab}{}
```

\NAT@wrout The original \NAT@wrout writes to aux file the information from the bbl file. Here we check whether we need to do this and whether to write the number:

```
375 \renewcommand{\NAT@wrout}[5]{%
376   \if@filesw
377     \ifx\NMBIB@current@type\NMBIB@bibtcite@type
378       {\let\protect\noexpand\let`\relax
379        \immediate
380        \write\@auxout{\string\bibcite{#5}{{#1}{#2}{#3}{#4}}}\fi
381     \ifNMBIB@writenumber
382       {\let\protect\noexpand\let`\relax
383        \immediate
384        \write\@auxout{\string\nmbibcitenumber{#5}{#1}}}\fi
385   \fi
386   \ignorespaces}
```

\NAT@anchor The command \NAT@anchor{\langle KEY\rangle}{\langle text\rangle} creates a hyperlink if the package `hyperref` is loaded. Here we redefine it to create cites in the style KEY-TYPE:

```
387 \def\NAT@anchor#1#2{%
388   \hyper@natanchorstart{#1@\extra@b@citeb-\NMBIB@current@cite@suffix}%
389   \def\@tempa{#2}\@ifx{\@tempa\@empty}{}{\@biblabel{#2}}%
390   \hyper@natanchorend
391 }
```

\nmbibSetBiblabel Setting biblabel for the list

```
392 \def\nmbibSetBiblabel#1#2{%
393   \expandafter\def\csname NMBIB@#1@biblabel\endcsname##1{#2}}
```

\NMBIB@timeline@biblabel The default labels

```
394 \nmbibSetBiblabel{timeline}{[\nmbibDATE:
395   \nmbibLink{\nmbibKEY}{authors}{\nmbibNAME};
396   \nmbibLink{\nmbibKEY}{sequence}{\nmbibNUM}]}
397 \nmbibSetBiblabel{authors}{[\nmbibNAME\
398   (\nmbibLink{\nmbibKEY}{timeline}{\nmbibDATE});
399   \nmbibLink{\nmbibKEY}{sequence}{\nmbibNUM}]}
400 \nmbibSetBiblabel{sequence}{[\nmbibNUM:
401   \nmbibLink{\nmbibKEY}{authors}{\nmbibNAME}
402   (\nmbibLink{\nmbibKEY}{timeline}{\nmbibDATE})]}
```

3.6 Ending the Style

```
403 </style>
```

Sequential List of References

- [1: Cohen et al. (2013a)] Michael Cohen, Yannis Haralambous, and Boris Veytsman. *The Multibibliography package*, March 2013. <http://www.ctan.org/pkg/multibibliography>.
- [2: Cohen et al. (2013b)] Michael Cohen, Yannis Haralambous, and Boris Veytsman. The multibibliography package. *TUGboat*, 34(3):340–343, 2013. <https://www.tug.org/members/TUGboat/tb34-3/tb108cohen.pdf>.
- [3: Daly (2009)] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [4: Rahtz and Oberdiek (2012)] Sebastian Rahtz and Heiko Oberdiek. *Hypertext Marks in L^AT_EX: a Manual for Hyperref*, November 2012. <http://mirrors.ctan.org/macros/latex/contrib/hyperref>.

Alphabetic List of References

- [Cohen et al. (2013a); 1] Michael Cohen, Yannis Haralambous, and Boris Veytsman. *The Multibibliography package*, March 2013. <http://www.ctan.org/pkg/multibibliography>.
- [Cohen et al. (2013b); 2] Michael Cohen, Yannis Haralambous, and Boris Veytsman. The multibibliography package. *TUGboat*, 34(3):340–343, 2013. <https://www.tug.org/members/TUGboat/tb34-3/tb108cohen.pdf>.
- [Daly (2009); 3] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [Rahtz and Oberdiek (2012); 4] Sebastian Rahtz and Heiko Oberdiek. *Hypertext Marks in L^AT_EX: a Manual for Hyperref*, November 2012. <http://mirrors.ctan.org/macros/latex/contrib/hyperref>.

Chronological List of References

- [2009: Daly; 3] Patrick W. Daly. *Natural Sciences Citations and References (Author-Year and Numerical Schemes)*, February 2009. <http://mirrors.ctan.org/macros/latex/contrib/natbib>.
- [2012: Rahtz and Oberdiek; 4] Sebastian Rahtz and Heiko Oberdiek. *Hypertext Marks in L^AT_EX: a Manual for Hyperref*, November 2012. <http://mirrors.ctan.org/macros/latex/contrib/hyperref>.

- [2013b] Cohen et al.; 2] Michael Cohen, Yannis Haralambous, and Boris Veytsman.
The multibibliography package. *TUGboat*, 34(3):340–343, 2013. <https://www.tug.org/members/TUGboat/tb34-3/tb108cohen.pdf>.
- [2013a] Cohen et al.; 1] Michael Cohen, Yannis Haralambous, and Boris Veytsman.
The Multibibliography package, March 2013. <http://www.ctan.org/pkg/multibibliography>.

Change History

v1.00		
	General: Preliminary release	1
v1.01		
	\NMBIB@sequence@biblabel: Punc-	
	tiuation changed	18
	\timelinerefname: Typo cor-	
	rected	16
v1.02		
	\@@lbitem: Added suppression of	
	suffixes	17
	\ifNMBIB@printyearsuffix:	
	Added macro	10
	\nmbibYearSuffixOff: Added	
	macro	10
	\nmbibYearSuffixOn: Added	
	macro	10
	\printbibliography: Added sup-	
	pression of suffixes	17
v1.03		
	General: Added day field in the	
	chrono bst	1
v1.04		
	\timelinebibname: Typo cor-	
	rected	16

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@CQ	71
\@CQ@citeall ...	313, 314
\@CQciteall ...	312, 313
\@CQlbibitem ...	364, 365
\@auxout	380, 384
\@begindocumenthook	32, 40
\@biblabel	59, 352, 389
\@bibsetup	60
\@cite .	57, 112, 219, 318
\@cited	131,
	147, 165, 192,
	197, 212, 224,
	238, 253, 262,
	263, 264, 269,
	284, 292, 293,
	294, 323, 334, 335
\@citeall	311, 312
\@citedb	71, 113, 115,
	117, 120, 122,
	123, 125, 190,
	205, 220, 222,
	224, 227, 229,
	230, 232, 256,
	287, 319, 321,
	323, 326, 327, 330
\@citex	58, 304
\@empty	
	62, 70, 112, 115,
	219, 222, 321, 389
\@extra@b@citedb ...	
	106, 117,
	123, 125, 205,
	224, 230, 232,
	256, 287, 323, 388
\@extra@binfo	
	83, 87, 91, 103, 104
\@firstofone	
	115, 222, 321
\@for	15, 17,
	21, 28, 44, 50,
	71, 73, 113, 220, 319
\@ifnextchar	
	311, 312, 313, 364
\@ifnum	78, 130, 132,
	134, 141, 142,
	145, 157, 180, 182
\@ifundefined	
	83, 103, 117,
	123, 224, 230, 323
\@ifx	389
\@input@	362
\@lbibitem	372
\@namedef	87, 125, 232
\@ne	130,
	142, 144, 157, 165
\@onlypreamble	14
\@safe@activesfalse	116, 223, 322
\@safe@activestrue	114, 221, 320
\@tempa	15,
	16, 17, 18, 21,
	22, 23, 24, 28,
	29, 44, 45, 50,
	51, 52, 73, 75, 389
\@tempcnta ...	139,
	140, 141, 144, 145
\@tempswafalse	157
\@tempswattrue	156
\@undefined	32, 40
\sqcup	397
A	
\advance	144
\AtBeginDocument	19, 33, 41
\AtEndDocument ..	26, 88
\authorsbibname ..	5, 342
\authorsrefname ..	5, 341
B	
\begingroup	311
\bfseries	118, 225, 324
C	
\citation	76
\citeall	4, 310
\citealn	4, 305
\citenum	305
\citenumfont	168, 206, 212
\closeout	29
\csname	13, 18,
	22, 23, 24, 29,
	36, 45, 51, 55,
	75, 91, 104, 106,
	352, 353, 354,
	360, 361, 362, 393
\CurrentOption	8
D	
\DeclareOption	8
\DeclareRobustCommand	310
\def	11, 12, 31,
	39, 48, 53, 54,
	56, 64, 67, 68,
	82, 90, 103, 105,
	108, 112, 137,
	189, 191, 196,
	201, 211, 214,
	227, 243, 273,
	306, 312, 313,
	314, 326, 335,
	345, 348, 350,
	351, 352, 356,
	358, 363, 364,
	365, 368, 373,
	387, 389, 392, 393
\def@NAT@last@yr	
	147, 149, 201

\do	15, 17, 21, 28, 44, 50, 71, 73, 113, 220, 319	\hyper@natanchorstart	388	\MessageBreak .. 246, 247, 276, 277
	E		\hyper@natlinkbreak	255, 286	\multibibliography 3, 39 \multibibliographyfilename
\edef	13, 51, 55, 104, 115, 222, 321, 330, 331, 332, 333, 353, 360, 361, 369, 370, 371		\hyper@natlinkend	107, 207	\multibibliographystyle 4, 31
\else	32, 40, 92, 127, 148, 162, 164, 167, 181, 183, 234, 240, 249, 252, 266, 270, 279, 283, 286, 298, 302, 303, 328, 336, 357, 373		\hyper@natlinkstart	106, 205	
\endcsname	.. 13, 18, 22, 23, 24, 29, 36, 45, 52, 55, 75, 91, 104, 107, 352, 353, 354, 360, 361, 362, 393		I		N
\expandafter 13, 16, 18, 33, 41, 51, 55, 71, 74, 76, 79, 91, 115, 222, 321, 393		\if .. 167, 183, 237, 268, 286, 296, 302, 303, 336		\NAT@close .. 185, 303 \NAT@open .. 165, 286
	F		\if@files .. 20, 27, 35, 43, 72, 376		\NAT@alias .. . 132, 175, 264, 294
\fi	25, 30, 34, 38, 42, 47, 77, 98, 99, 126, 128, 150, 158, 166, 167, 176, 177, 183, 186, 233, 235, 247, 251, 260, 261, 265, 277, 282, 286, 290, 291, 295, 300, 301, 302, 303, 329, 336, 359, 373, 380, 384, 385		\if@tempswa .. 158		\NAT@call@names 124, 127, 231, 234, 328
	G		\ifcase .. 163, 236, 267		\NAT@anchor .. 387 \NAT@aysep .. 256
\gdef 48		\ifNAT@full .. 127, 234, 328		\NAT@biblabel .. 59
\global	... 87, 125, 232		\ifNAT@longnames .. 123, 230		\NAT@bibsetup .. 60
	H		\ifNAT@swa .. 93, 129, 181, 236, 302		\NAT@cite .. 57 \NAT@cite@list .. 70, 76, 79, 113, 220, 319
\hyper@natanchorend	390		\ifNMBIB@printyearsuffix .. 65, 373		\NAT@citea@mbox 158, 211
			\ifNMBIB@writenumber .. 343, 381		\NAT@citemultiple .. 84
			\ifx .. 32, 40, 91, 146, 164, 241, 242, 244, 271, 272, 274, 355, 377		\NAT@citeundefined .. . 119, 225, 324
			\ignorespaces .. 386		\NAT@citex .. 58
			\immediate .. 22, 24, 29, 36, 45, 74, 379, 383		\NAT@citexnum .. 108
			J		\NAT@close .. 63
			\jobname .. 16		\NAT@cmprs .. 134, 180
					\NAT@cmct .. 183, 302, 336
					\NAT@ctype .. 130, 132, 163, 171, 173, 182, 236, 267
					\NAT@date 63, 227, 237,
					239, 250, 258, 263, 268, 281, 288, 293, 296, 303, 326, 331, 369
					\NAT@def@citea .. . 161, 194, 265, 297
					\NAT@def@citea@box .. 169
					\NAT@def@citea@close .. . 299
					\NAT@def@citea@space .. . 199
					\NAT@exlab .. 244, 248, 274, 278, 358, 374
					\NAT@fullfalse .. 311
					\NAT@fulltrue .. 311

\NAT@hyper@citea@space	\NAT@super@kern	165	\NMBIB@hyper@citea@space
.....	173, 175		171, 196	
\NAT@idxtxt	\NAT@swafalse	93	\NMBIB@printyearsuffixfalse
				68
\NAT@ifcat@num	\NAT@temp	90, 91,	\NMBIB@printyearsuffixtrue	
135, 138	243, 244, 273, 274			
\NAT@last@nm	\NAT@test			
121, 164, 228, 241, 271	132, 165, 171, 173		
\NAT@last@num	\NAT@wrount	375	\NMBIB@sequence@aux	17
.			\NMBIB@sequence@biblabel	
121, 138, 139, 157	\NAT@year			394
\NAT@last@yr	219, 228, 242, 272	\NMBIB@sequence@cite@suffix	
.	\NAT@yrsep	164, 241, 271		
112, 146, 180, 202, 228, 242, 272	\natexlabel			50, 205
\NAT@last@yr@mbox	64, 363, 366, 373	\NMBIB@setup@authors	
142, 152	\nate xlabel@real			
\NAT@mbox	356, 358, 366	\NMBIB@setup@sequence	
165, 168, 185	\NeedsTeXFormat	1		348
\NAT@merge	\newcommand	89, 305	\NMBIB@setup@timeline	
142, 157	\newif	65, 343		
\NAT@name	\newwrite	18		347
63, 124, 128, 231, 235, 329, 370	\NMBIB@authors@filename		\NMBIB@testnum	88, 89
\NAT@nm	15	\NMBIB@timeline@aux	17
112, 121, 127, 128, 136, 137, 141, 145, 164, 219, 228, 234, 235, 238, 241, 254, 262, 269, 271, 285, 292, 328, 329, 332	\NMBIB@sequence@filename		\NMBIB@timeline@biblabel	
	15		394
\NAT@nmfmt	\NMBIB@timeline@filename		\NMBIB@timeline@cite@suffix	
238, 254, 262, 269, 285, 292	15		50
\NAT@num	\NMBIB@authors@cite@suffix		\NMBIB@types	
103, 104, 112, 121, 135, 136, 157, 168, 206, 212, 333, 371	50	11, 15, 17, 21, 28, 44, 50, 73	
\NAT@open	\NMBIB@authors@aux	17	\NMBIB@writenumberfalse	
63				
\NAT@parse	\NMBIB@authors@biblabel		\NMBIB@writenumbertrue	
101, 122, 229, 327, 367	394		
\NAT@parse@orig	\NMBIB@authors@cite@suffix			349
101, 102	50	\nmbibBasetype	6, 48
\NAT@penalty	\NMBIB@bibcite@type		\nmbibcitenumber	82, 384
62, 149, 164	48, 355, 377	\nmbibDATE	308, 331, 369, 394, 398, 402
\NAT@reset@citea	\NMBIB@citeallformat		\nmbibKEY	307,
111, 218, 317	306, 334	308, 309, 330,	
\NAT@reset@parser	\NMBIB@citex		368, 395, 396,	
109, 216, 315	214	398, 399, 401, 402	
\NAT@set@cites	\NMBIB@current@cite@suffix		\nmbibLink	5, 105,
56	353, 388	190, 307, 308,	
\NAT@sort	\NMBIB@current@type		309, 395, 396,	
78	351, 355, 377	398, 399, 401, 402	
\NAT@sort@cites	\NMBIB@hyper@	132,	\nmbibNAME	307, 332,
.	168, 189, 193,	370, 395, 397, 401	
69, 110, 217, 316	198, 212, 238,		
\NAT@sort@cites@	239, 248, 250,	\nmbibNUM	309, 333,
79	253, 258, 262,	371, 396, 399, 400	
\NAT@space	263, 264, 269,	\nmbibRedirectLinks	
61, 164	278, 281, 284,		5, 54
\NAT@spacechar	288, 292, 293, 294	\nmbibSetBiblabel	7,
61, 63, 165, 167, 249, 256, 280, 286			392, 394, 397, 400
\NAT@star@cite	\NMBIB@hyper@citea	191		

\nmbibSetCiteall	6 , 306	\ProcessOptions	9	\sequencerefname	5 , 339
\nmbibYearSuffixOff		\protect	378 , 382	\space	120 , 227 , 326
.....	7 , 68	\protected@edef	202	\string
\nmbibYearSuffixOn	7 , 67	\providecommand	...	37	46 , 76 , 380 , 384
\noexpand			
	204 , 205 ,	337	, 338 , 339 ,		
	206 , 207 , 378 , 382	340	, 341 , 342 , 374	T	
O		\ProvidesFile	3	\thepage	120 ,
\openout	22	\ProvidesPackage	5	227	, 245 , 275 , 326
\or	170 , 172 ,	R		\timelinebibname	5 , 338
	174 , 262 , 263 ,	\refname	360	\timelinerefname	5 , 337
	264 , 292 , 293 , 294	\relax	9 , 24 , 83 , 101 ,	\tw@	132
P			112 , 139 , 146 ,		
\PackageWarning	...		157 , 237 , 268 ,	U	
	119 , 226 , 325	\renewcommand	296 , 303 , 378 , 382	\unskip	249 , 280
\PackageWarningNoLine		W	
	85 , 94 , 244 , 274	\RequirePackage	10	\write	24 ,
\PassOptionsToPackage	...	\reset@font	118 , 225 , 324	36	, 45 , 74 , 380 , 384
	8	S		Z	
\printbibliography	...	\sequencebibname	5 , 340	\z@	78 , 134 , 180 , 182
	5 , 350				